

SHOP SMART. SHOP VALUE SHOP differently





E&E LED BOX EXIT BODY ONLY - WALL / CEILING DIFFUSER

PRODUCT RANGE					
CODE	DESCRIPTION	Carton Qty			
CS-EXWAYBOX	E&E LED Box Exit Body Only	6 pieces			
CS-DWAYBOXW	E&E Wall Diffuser to suit EXWAYBOX	6 pieces			
CS-DWAYBOXC	E&E Ceiling Diffuser to suit EXWAYBOX	4 pieces			





ORDERING INFO	DRMATION	
PRODUCT	WEIGHT	DIMENSION (L X W X H)
Body Only	0.9kg (unit) - 4.8kg (box)	380mm x 65mm x 160mm
Wall Diffuser	0.5kg (unit) - 3.0kg (box)	380mm x 89mm x 160mm
Ceiling Diffuser	1.0kg (unit) - 4.0kg (box)	380mm x 160mm x 206mm

TECHNICAL SPECIFICATIONS				
Operating Mode	Switch Maintained			
Voltage (V); Frequency (Hz)	220-260V; 50Hz			
Operating Temperature	1° - 45° C			
IP Rating	IP20			
Wiring	Large Terminal Block			
Mountain Type	Wall or Ceiling Surface Mount			
Testing System	Manual Test Switch			
Construction	Polycarbonate Body and Diffuser			
Classification	C0 D4 C90 D2.5 (Wall)			
	C0 D8 C90 D6.3 (Ceiling)			
Standards	AS/NZ 2293			
	AS/NZS 60598.1			
	EMC			

BATTERY AND LEDS	
Battery	High-Temp LiFePO4 Lithium Battery
Power Consumption	4W
Charging Method	3 Stage Intelligence
Charging Time	16 Hours
Lens	LED Lamp Rated 50,000 hours
Viewing Distance	24 Metres

REPLACEMENT PART				
PART NUMBER	DESCRIPTION			
BWAYBOX	LiFePO4 Lithium Battery, 3.2V 1500mAh			

SPACING TABLE AND MOUNTING HEIGHT									
CLASSIFICATION	2.1m	2.4m	2.7m	3m	3.3m	3.6m	4m	4.5m	5m
D4	7.1	7.2	7.3	7.3	7.2	7.1	6.9	0.0	0.0
D8	9.4	9.7	9.9	10.1	10.2	10.3	10.3	10.3	10.1
D2.5	5.8	5.8	5.7	5.6	5.3	0.0	0.0	0.0	0.0
D6.3	8.5	8.8	8.9	9.1	9.1	9.2	9.1	9.0	8.7

