
Emerex Wall Box Emergency Exit Light Non Arrow





MODEL	CS-MRX-EXWPW-NONARROW	**IK**	10
LED BRAND	Osram	**OPERATING TEMPERATURE (°C)**	0 – 40°C
DRIVER BRAND	SYNNOVATE	**MAINTAINED/NON-MAINTAINED OPERATION**	Switchable in between
INPUT VOLTAGE (V)	230V	**DIMMABLE**	NA
POWER FACTOR (PF)	0.95	**VIEWING (m)**	24
WATTAGE (W)	2W	**INSTALLATION TYPE**	Surface Mount - Wall
FLICKER FREE	YES	**DIMENSION (mm)**	375 x 135 x 185
LUMEN OUTPUT (LM)	>30LM	**NET WEIGHT (kg)**	2.5
EFFICACY (LM/W)	>15LM/W	**LIFESPAN (Hours)**	50,000
HOUSING COLOUR & MATERIAL	White, ABS	**WARRANTY (Years)**	3
IP	67	**COMPLIANCE**	AS/NZS 2293, AS/NZS 60598, RCM

Yiyun Corporation Pty Ltd | ABN 39 074 449 988 | All information provided in this catalogue is subject to change at business discretion. Please contact the office for confirmation of pricing and stock availability at the time of order.