
JINHANG 6th Version SMD LED Floodlight 50W Clear





MODEL	JH-FL6-50W-3000K-CLEAR JH-FL6-50W-5700K-CLEAR	**FINISH & MATERIAL**	Aluminum, Black
INPUT VOLTAGE (V)	176-280V AC	**IP**	IP66
PROTECTION CALSS	Class I	**IK**	IK06
SPD (KV)	2.5KV	**OPERATING TEMPERATURE (°C)**	-25℃ to +45℃
POWER FACTOR (PF)	0.9	**DIMMABLE**	No
WATTAGE (W)	50W	**INSTALLATION TYPE**	Surface Mount
LUMEN OUTPUT (Lm)	4,000 Lm	**DIMENSION (mm)**	L236 x H297 x D44 mm
EFFICACY (Lm/W)	80 Lm/W	**NET WEIGHT (Kg)**	2.19 Kg
COLOUR TEMPERATURE	3000K / 5700K	**LIFESPAN (Hr.)**	30,000 Hrs.
BEAM ANGLE (°)	120°	**WARRANTY (Yr.)**	3 Yrs.
CRI (Ra)	80	**COMPLIANCE**	SAA

MOORABBIN
97 Cochranes Road,
Moorabbin VIC 3189

ALTONA
1 Drake Boulevard,
Altona VIC 3018

ALBION
35 Sandgate Road,
Albion QLD 4010

sales@jinhang.com.au
www.jinhang.com.au

Victoria: 1300 000 808
Queensland: 1300 000 707

Yiyun Corporation Pty Ltd | ABN 39 074 449 988 | All information provided in this catalogue is subject to change at business discretion. Please contact the office for confirmation of pricing and stock availability at the time of order.