

Emerex Wall/Ceiling 4ft Wireguard Fitting with Self Test





Product Specification

MODEL	CS-MRX-WG122-EMERGENCY-ST	**HOUSING COLOUR & MATERIAL**	White, Powder Coat Folded Sheet Metal
LED BRAND	Osram	**IP**	20
DRIVER BRAND	SYNNOVATE	**IK**	09
INPUT VOLTAGE (V)	230V	**EMERGENCY DURATION (minutes)**	>120
POWER FACTOR (PF)	0.95	**OPERATING TEMPERATURE (°C)**	0 to +40 °C
WATTAGE (W)	2x18W	**MAINTAINED/NON-MAINTAINED OPERATION**	Switchable between maintained and non-maintained
FLICKER FREE	YES	**DIMMABLE**	YES
LUMEN OUTPUT (LM)	4,000 LM	**INSTALLATION TYPE**	Surface Mount – Wall / Ceiling
EFFICENCY (LM/W)	111 LM/W	**DIMENSION (mm)**	1270 x 130 x 110
CCT (K)	4000K	**NET WEIGHT (kg)**	3
CRI	>80	**LIFETIME (Hour)**	50,000
BEAM ANGLE (°)	120°	**WARRANTY (Year)**	3
COMPLIANCE		AS/NZS 2293, AS/NZS 60598, RCM	