

Emerex Wall/Ceiling 4ft WP Emergency Fitting with Sensor





MODEL	CS-MRX-EMWP122-S	**IK**	10
LED BRAND	Osram	**OPERATING TEMPERATURE (°C)**	0 - 40°C
DRIVER BRAND	SYNNOVATE	**MAINTAINED/NON-MAINTAINED**	Switchable (between maintained and non-maintained)
INPUT VOLTAGE (V)	230V	**Sensitivity**	8m
POWER FACTOR (PF)	0.95	**Duration**	30s to 10min
WATTAGE (W)	40	**3 Stage Microwave Dimming Senor**	0%, 10%, 20%, 30% 1) ON at full brightness 2) after a while without motion (e.g. 3 min), it dims down to set level (e.g. 10%) 3) after a while at dimmed state, there is a further option to completely turn the light off (e.g. after 60mins, it goes to 0%)
FLICKER FREE (Y/N)	YES	**DIMMABLE (Y/N)**	YES
LUMEN OUTPUT (LM)	3,800LM	**INSTALLATION TYPE**	Surface Mount – Wall / Ceiling
EFFICACY (LM/W)	95LM/W	**CUT-OUT (mm)**	N/A
COLOUR TEMPERATURE	4000K	**DIMENSION (mm)**	1260 x 120 x 70
BEAM ANGLE (°)	120°	**NET WEIGHT (kg)**	2
CRI (Ra)	84	**LIFESPAN (Hours)**	50,000
HOUSING COLOUR & MATERIAL	White, Polycarbonate + Acrylic Diffuser	**WARRANTY (Years)**	3
IP	65	**COMPLIANCE**	AS/NZS 2293, AS/NZS 60598, RCM