
JINHANG Floodlight V7 30W Sensor White





MODEL	CS-JH-FL13-30-Sensor-W	**CRI (Ra)**	80
LED BRAND & TYPE	Osram	**SDCM**	<5
DRIVER BRAND & TYPE	Driver on board	**HOUSING COLOUR & MATERIAL**	White, Magnesium-aluminum alloy/ tempered glass
SENSOR DETECTION AREA	8~10m	**SENSOR DETECTION ANGLE**	150°
SENSOR HOLD TIME	1min±10s	**INPUT VOLTAGE (V)**	AC 220-240V
IP	IP66	**PROTECTION CLASS**	Class I
IK	IK07	**SPD (KV)**	4KV
POWER FACTOR (PF)	≥0.99	**AMBIENT TEMPERATURE (°C)**	40℃
WATTAGE (W)	30W	**OPERATING TEMPERATURE (°C)**	-40℃～+40℃
FLICKER FREE	/	**DIMMABLE (Y/N)**	N
LUMEN OUTPUT (LM)	2,700 LM @4000K 3,000 LM @5000K	**INSTALLATION TYPE**	Bracket Mount
EFFICACY (LM/W)	90 LM/W @4000K 100 LM/W @5000K	**DIMENSION (mm)**	L145×W115×H21mm
COLOUR TEMPERATURE	4000K / 5000K	**NET WEIGHT (kg)**	0.43Kg±0.1Kg
BEAM ANGLE (°)	120°	**LIFESPAN (hr.)**	≥100,000 hrs.
WARRANTY (yr.)	3 yrs.	**COMPLIANCE**	SAA

Yiyun Corporation Pty Ltd | ABN 39 074 449 988 | All information provided in this catalogue is subject to change at business discretion. Please contact the office for confirmation of pricing and stock availability at the time of order.