



SHOP SMART. SHOP VALUE

SHOP *differently*



MSZ-AP Series (Wall Mounted)									
Indoor Unit			MSZ-AP20VG	MSZ-AP25VG(D*)	MSZ-AP35VG(D*)	MSZ-AP42VG(D*)	MSZ-AP50VG(D*)		
Outdoor Unit			MUZ-AP20VG	MUZ-AP25VG(D*)	MUZ-AP35VG(D*)	MUZ-AP42VG(D*)	MUZ-AP50VG(D*)		
Refrigerant			R32						
Cooling	Capacity [Rated]	kW	2.00	2.50	3.50	4.20	5.00		
	Capacity [Min-Max]	kW	0.60 - 2.70	1.10 - 3.60	1.10 - 4.10	0.90 - 4.80	1.40 - 6.20		
	Total Input [Rated]	kW	0.46	0.50	0.87	1.19	1.32		
	Total Input [Min-Max]	kW	0.23 - 1.16	0.21 - 0.99	0.21 - 1.18	0.15 - 1.90	0.30 - 2.23		
	EER		4.35	5.00	4.02	3.53	3.79		
	AEER		4.31	4.97	4.01	3.52	3.78		
	Star Rating		3.5	5.5	3.5	2.5	3.0		
	Running Current [Rated]	A	2.60			4.10	5.30	5.90	
	Sound Pressure Level	In [Quiet-Lo-Mid-Hi-SHi]	dB(A)	21 - 26 - 30 - 35 - 42	19 - 24 - 31 - 38 - 44	19 - 24 - 31 - 38 - 45	26 - 29 - 35 - 40 - 46	28 - 33 - 39 - 44 - 49	
		Out [PWL]	dB(A)	47 (59)	46 (59)	50 (64)	51 (65)	54 (69)	
Air Volume (In) [Quiet-SHi]	L/S		58 - 115	82 - 205	82 - 223	90 - 223	100 - 258		
Heating	Capacity [Rated]	kW	2.50	3.20	3.70	5.40	6.00		
	Capacity [Min-Max]	kW	0.50 - 3.50	1.30 - 5.00	1.30 - 5.10	1.30 - 6.00	1.40 - 8.00		
	Total Input [Rated]	kW	0.60	0.67	0.81	1.43	1.62		
	Total Input [Min-Max]	kW	0.25 - 1.20	0.35 - 1.40	0.35 - 1.42	0.26 - 1.90	0.30 - 3.00		
	COP		4.17	4.78	4.57	3.78	3.70		
	ACOP		4.14	4.75	4.55	3.77	3.70		
	Star Rating		3.0	5.0	4.5	3.0	3.0		
	Running Current [Rated]	A	3.20	3.30	3.80	6.30	7.10		
	Sound Pressure Level	In [Quiet-SHi]	dB(A)	21 - 26 - 30 - 35 - 42	18 - 25 - 31 - 38 - 42	19 - 25 - 31 - 38 - 45	26 - 29 - 35 - 40 - 46	28 - 33 - 38 - 43 - 48	
		Out [PWL]	dB(A)	48 (61)	49 (59)	50 (64)	52 (65)	56 (69)	
	Air Volume (In) [Quiet-SHi]	L/S		62 - 122	82 - 190	82 - 215	88 - 233	93 - 268	
	Input [Rated] (Cooling/Heating)	W		19/19	23/19	29/26	29/33	43/43	
	Indoor Unit	Dimensions [HxWxD]	mm	250 x 760 x 178	299 x 798 x 219				
		Weight	kg	8.2	10.5				
Outdoor Unit	Dimensions [HxWxD]	mm	550 x 800 x 285					714 x 800 x 285	
	Weight	kg	31.0	34.0/35.0			35.0/36.0	40.0/41.0	
Piping	Breaker Size	A	10					16	
	Diameter [Gas/Liquid]	mm	ø9.52/ø6.35					ø12.70/ø6.35	
	Max. Length/Height	m	20/12						
Guaranteed Operating Range [Outdoor]	Cooling	°C	-10 ~ 46						
	Heating	°C	-15 ~ 24						
Refrigerant Amount [Pre-Charged]		kg	0.55	0.70				1.00	

Notes:

- Nominal conditions cooling: EAT 27°CDB/19°CWB, Ambient 35°CDB. Rated conditions cooling: EAT 24°CDB/17°CWB, Ambient 35°CDB.
Nominal conditions heating: EAT 20°CDB/15°CWB, Ambient 7°CDB/6°CWB.
- Rated Load Amps (RLA) is based on nominal conditions. Use Maximum Circuit Amps (MCA) for power supply infrastructure sizing, etc.
(D*) represents DRED enabled model. This is only available in QLD.

Rating Conditions:

Cooling: Indoor 27°C, D.B./19°C, W.B.
Outdoor 35°C, D.B./24°C, W.B.
Heating: Indoor 20°C, D.B./15°C, W.B.
Outdoor 7°C, D.B./6°C, W.B.

Product Specifications



MSZ-AP Series (Wall Mounted)						
Indoor Unit			MSZ-AP60VG(D*)	MSZ-AP71VG(D*)	MSZ-AP80VG(D*)	
Outdoor Unit			MUZ-AP60VG(D*)	MUZ-AP71VG(D*)	MUZ-AP80VG(D*)	
Refrigerant			R32			
Cooling	Capacity [Rated]	kW	6.00	7.10	7.80	
	Capacity [Min-Max]	kW	1.40 - 7.30	2.00 - 8.70	2.00 - 9.20	
	Total Input [Rated]	kW	1.59	2.01	2.36	
	Total Input [Min-Max]	kW	0.24 - 2.35	0.43 - 3.03	0.43 - 3.20	
	EER		3.77	3.53	3.31	
	AEER		3.77	3.53	3.30	
	Star Rating		3.0	2.5	2.0	
	Running Current [Rated]	A	7.10	8.80	10.80	
	Sound Pressure Level	In [Quiet-Lo-Mid-Hi-SHi]	dB(A)	29 - 37 - 41 - 45 - 48	30 - 37 - 41 - 45 - 49	30 - 37 - 41 - 45 - 53
		Out [PWL]	dB(A)	55 (69)	56 (69)	
Air Volume (In) [Quiet-SHi]	L/S	156 - 315	160 - 310	160 - 343		
Heating	Capacity [Rated]	kW	6.80	8.00	9.00	
	Capacity [Min-Max]	kW	2.00 - 8.60	2.20 - 9.90	2.20 - 11.00	
	Total Input [Rated]	kW	1.67	2.09	2.55	
	Total Input [Min-Max]	kW	0.30 - 2.60	0.42 - 3.25	0.42 - 3.65	
	COP		4.07	3.83	3.53	
	ACOP		4.06	3.82	3.53	
	Star Rating		3.5	3.0	2.5	
	Running Current [Rated]	A	7.40	9.10	11.30	
	Sound Pressure Level	In [Quiet-SHi]	dB(A)	29 - 37 - 41 - 45 - 48	30 - 37 - 41 - 45 - 51	
		Out [PWL]	dB(A)	57 (69)	55 (69)	
	Air Volume (In) [Quiet-SHi]	L/S	180 - 338	133 - 320		
	Indoor Unit	Input [Rated] (Cooling/Heating)	W	45/49	42/45	55/45
Dimensions [HxWxD]		mm	325 x 1100 x 257			
Weight		kg	16.0	17.0		
Outdoor Unit	Dimensions [HxWxD]	mm	714 x 800 x 285	880 x 840 x 330		
	Weight	kg	40.0/41.0	55.0		
	Breaker Size	A	16	20		
Piping	Diameter [Gas/Liquid]	mm	ø12.70/ø6.35			
	Max. Length/Height	m	30/15			
Guaranteed Operating Range [Outdoor]	Cooling	°C	-10 ~ 46			
	Heating	°C	-15 ~ 24			
Refrigerant Amount [Pre-Charged]		kg	1.0		1.5	

Notes:

- Nominal conditions cooling: EAT 27°CDB/19°CWB, Ambient 35°CDB. Rated conditions cooling: EAT 24°CDB/17°CWB, Ambient 35°CDB.
Nominal conditions heating: EAT 20°CDB/15°CWB, Ambient 7°CDB/6°CWB.
- Rated Load Amps (RLA) is based on nominal conditions. Use Maximum Circuit Amps (MCA) for power supply infrastructure sizing, etc.
(D*) represents DRED enabled model. This is only available in QLD.

Rating Conditions:

Cooling: Indoor 27°C, D.B./19°C, W.B.
Outdoor 35°C, D.B./24°C, W.B.
Heating: Indoor 20°C, D.B./15°C, W.B.
Outdoor 7°C, D.B./6°C, W.B.



MOORABBIN

131-133 Keys Road
Moorabbin VIC 3189

ALTONA

1 Drake Boulevard
Altona VIC 3018

ALBION

35 Sandgate Road
Albion QLD 4010

AUCKLAND

10 Fairfax Avenue, Penrose
Auckland 1061, New Zealand

sales@jh.market

www.jh.market

sales@jhmarket.co.nz
jhmarket.co.nz

AU National: 1300 000 808

Queensland: 1300 000 707

NZ National: 0800 748 848

Yiyun Corporation Pty Ltd | All information in this catalogue is subject to change at business discretion.

Please contact the office for confirmation of pricing and stock availability at time of order