

JinHang 200W Floodlight V7 5000K





MODEL	CS-JH-FL13-200	**CRI (Ra)**	75
LED BRAND	Nichia	**SDCM**	<5
DRIVER BRAND	Driver on board	**HOUSING COLOUR & MATERIAL**	Black, Magnesium aluminum alloy/tempered glass
INPUT VOLTAGE (V)	AC 120-277V	**IP**	IP66
PROTECTION CALSS	Class I	**IK**	IK07
SPD (KV)	4	**AMBIENT TEMPERATURE (°C)**	40℃
POWER FACTOR (PF)	≥0.99	**OPERATING TEMPERATURE (°C)**	-40℃ ~ +40℃
WATTAGE (W)	200W	**DIMMABLE (Y/N)**	No
FLICKER FREE (Y/N)	Yes	**INSTALLATION TYPE**	Bracket Mount
LUMEN OUTPUT (LM)	24,000 LM	**DIMENSION (mm)**	L250 x W200 x H30 mm
EFFICACY (LM/W)	120 LM/W	**NET WEIGHT (kg)**	4.2Kg ±0.2
COLOUR TEMPERATURE	5000K	**LIFESPAN (hr.)**	≥100,000 hrs.
BEAM ANGLE (°)	120°	**WARRANTY (yr.)**	5 yrs.
COMPLIANCE		SAA	

Yiyun Corporation Pty Ltd | All information in this catalogue is subject to change at business discretion.
Please contact the office for confirmation of pricing and stock availability at time of order