TV32UV

UHF / VHF Combination Log Periodic Digital Antenna



Our DIGILOG™ and DIGILOGPLUS™ have **FEATURES** now been improved and are now heavy • Easy installation duty.

The DIGILOG™ log periodic antennas • Very low noise floor are built to pass the 216 hour salt • Horizontal or vertical mount spray test, the salt spray test creates • Evenly balanced across all channels artificial saline air/fog to simulate sea • No balun - perfectly matched to the signal side environments. This evaluates the • Requires less gain than traditional antennas active life.

In addition we have added an elastomer gasket to the F connector, as shown in the • Solid 5mm Aluminium Elements already picture. This silicon washer protects the strengthening the cable connection.

- RoHS compliant
- Salt Spray Test

- corrosion resistance of the antenna. Locks on to the strongest signal no ghosting issues
- This test simulates 10 years plus of Small, light-weight, no need for heavy costly hardware
 - Europe Standard Aluminium Antenna Carrier with Size 14x14mm
 - premounted with F connector
- F-connector from additional corrosion, Specially designed for the reception of digital TV channels in UHF/VHF

SPECIFICATIONS	
No.of Elements	32
Channels	Ch.1-12 Ch.21-69
Frequency Range	174-230MHz 470-862MHz
Antenna Gain	7.5-8.5dB
Beam Width H/V	H45°-55°/V55°-65°
Front-back Ratio	20-30dB
Impedance	75Ω