
LiteLighting 10W IC Downlight Tricolour 90mm Cut-out





MODEL	CS-LL-FDL3-IC-P9010D-CCT	**MATERIAL**	Polycarbonate
INPUT VOLTAGE (V)	220-240V AC	**IP**	IP44
IC-4 RATED (Y/N)	Yes	**OPERATING TEMPERATURE (°C)**	-20℃ to +45℃
POWER FACTOR (PF)	0.9	**DIMMABLE (Y/N)**	Yes
WATTAGE (W)	10W	**DIMMING TYPE**	TRIAC dimming
FLICKER FREE (Y/N)	Yes	**INSTALLATION TYPE**	Recessed
LUMEN OUTPUT (LM)	820LM	**CUT-OUT (mm)**	Ø90
EFFICACY (LM/W)	82LM/W	**DIMENSION (mm)**	Ø115*H68
COLOUR TEMPERATURE (K)	Tricolour: 3000K-4000K-6000K	**NET WEIGHT (kg)**	0.23
BEAM ANGLE (°)	120°	**LIFESPAN (hr.) @L70B50**	30,000
CRI (Ra)	>80	**WARRANTY (yr.)**	3
HOUSING COLOUR	White	**COMPLIANCE**	SAA, RCM

Yiyun Corporation Pty Ltd | All information in this catalogue is subject to change at business discretion.
Please contact the office for confirmation of pricing and stock availability at time of order