

LiteLighting 32W Tri-colour Non-dimmable Backlit LED Panel 295x1195





MODEL	CS-LL-PL03-30120ND-32W-CCT	**HOUSING COLOUR**	White
INPUT VOLTAGE (V)	AC 220-240V	**MATERIAL**	PS+AL+SPCC
IC-4 RATED (Y/N)	NO	**IP**	20
POWER FACTOR (PF)	>0.9	**OPERATING TEMPERATURE (°C)**	0~40°C
WATTAGE (W)	32W	**DIMMABLE (Y/N)**	NO
FLICKER FREE (Y/N)	YES	**DIMMING TYPE**	NA
LUMEN OUTPUT (LM)	3,520LM	**INSTALLATION TYPE**	Recessed
EFFICACY (LM/W)	110LM/W	**HOLE OUT (mm)**	256*1156
COLOUR TEMPERATURE (K)	Tri-colour: 3000K/4000K/5700K	**DIMENSION (mm)**	295*1195*34.5
BEAM ANGLE (°)	110°	**NET WEIGHT (kg)**	1.9
CRI (Ra)	80	**LIFESPAN (Hours)**	50,000
SDCM	5	**WARRANTY**	3 years
UGR	22	**COMPLIANCE**	SAA, RCM

Yiyun Corporation Pty Ltd | All information in this catalogue is subject to change at business discretion.
Please contact the office for confirmation of pricing and stock availability at time of order