
# JinHang LED Floodlight V7 - 50W, 5000K



| | | | |
|---|---|---|---|
| **MODEL** | CS-JH-FL13-50 | **CRI (Ra)** | 75 |
| **LED BRAND** | Nichia | **SDCM** | <5 |
| **DRIVER BRAND** | Driver on board | **HOUSING COLOUR & MATERIAL** | Black, Magnesium aluminum alloy/tempered glass |
| **INPUT VOLTAGE (V)** | AC 120-277V | **IP** | IP66 |
| **PROTECTION CALSS** | Class I | **IK** | IK07 |
| **SPD (KV)** | 4 | **AMBIENT TEMPERATURE (°C)** | 40°C |
| **POWER FACTOR (PF)** | ≥0.99 | **OPERATING TEMPERATURE (°C)** | -40°C ~ +40°C |
| **WATTAGE (W)** | 50W | **DIMMABLE (Y/N)** | No |
| **FLICKER FREE (Y/N)** | Yes | **INSTALLATION TYPE** | Bracket Mount |
| **LUMEN OUTPUT (LM)** | 4,500 LM @4000K<br>5,000 LM @5000K | **DIMENSION (mm)** | L200 x W160 x H30 mm |
| **EFFICACY (LM/W)** | 90 LM/W @4000K<br>100 LM/W @5000K | **NET WEIGHT (kg)** | 1.0Kg ±0.1 |
| **COLOUR TEMPERATURE** | 4000K / 5000K | **LIFESPAN (hr.)** | ≥100,000 hrs. |
| **BEAM ANGLE (°)** | 120° | **WARRANTY (yr.)** | 3 yrs. |
| **COMPLIANCE** | | SAA | |



Yiyun Corporation Pty Ltd | All information in this catalogue is subject to change at business discretion.
*Please contact the office for confirmation of pricing and stock availability at time of order*