
Rafe 33W Surface Mount Downlight IP65 WH





SKU	CS-CGD-LC1518R-01-33W-3000K-60D-IP65-WH CS-CGD-LC1518R-01-33W-4000K-60D-IP65-WH CS-CGD-LC1518R-01-33W-5000K-60D-IP65-WH	**UGR**	19
LED BRAND AND TYPE	Bridgelux COB	**HOUSING COLOUR**	WHITE
INPUT VOLTAGE (V)	220-240V; 50/60Hz	**MATERIAL**	ALUMINUM
PROTECTION CALSS	CLASS I	**IP**	65
IC-4 RATED (Y/N)	YES	**IK**	N/A
POWER FACTOR (PF)	0.9	**OPERATING TEMPERATURE (°C)**	-20°C to +40°C
WATTAGE (W)	33W	**DIMMABLE (Y/N)**	Yes
FLICKER FREE (Y/N)	YES	**DIMMING TYPE**	Traic-dimming
LUMEN OUTPUT (LM)	2970LM	**INSTALLATION TYPE**	SURFACE MOUNTED
EFFICACY (LM/W)	90LM/W	**DIMENSION (mm)**	Ø135 x H170 mm
COLOUR TEMPERATURE (K)	3000K / 4000K / 5000K	**NET WEIGHT (kg)**	1.6
BEAM ANGLE (°)	60°	**LIFESPAN (HOURS)**	50,000
CRI (Ra)	90	**WARRANTY (YEARS)**	3
SDCM	3	**COMPLIANCE**	SAA, RCM

Yiyun Corporation Pty Ltd | All information in this catalogue is subject to change at business discretion.
Please contact the office for confirmation of pricing and stock availability at time of order