JinHang Dot-Free COB Strip Light 24V 10W/M IP20 5M 3000K
JH-SS-COB-320D-24V-5m8mm-3000K


COB flex strip



Description

COB strips are fixed directly on the PCB through solder paste using flip-chip, which shortens the heat dissipation path. The heat emitted by the LED chips is spread to the PCB through the solder paste directly which make the heat dissipation effect much better than the normal SMD strips, with a maximum 180 ° viewing angle to achieve more continuous and dot-free light.

Dimensions



General data

Voltage(V)	DC24
Power(W/m)	10
Length/reel(m)	5
PCB width(mm)	8
Copper foil	2OZ
Chips/m	320
Max. length per input(m)	5
Cutting interval(mm)	50
Electrical protection	Class III
Dimmable	YES
Operate temperature	-20 ~ 40℃
Warranty	3 Years

Mark:The tolerance of output data can be vary up to 10%


Optical data


Lumen(lm/m)	800lm@2700K,850lm@3000K,900lm@4000K&6500K
Efficacy (lm/W)	80@2700K,85@3000K,90@4000K&6500K
Colour temperature (K)	2700/3000/4000/6500
CRI (Ra)	>90
R9	>50
Beam Angle (°)	140
Distribution type	Symmetric

Mark:The tolerance of output data can be vary up to 10%


Yiyun Corporation Pty Ltd | All information in this catalogue is subject to change at business discretion.
Please contact the office for confirmation of pricing and stock availability at time of order

Photometric data





Packing



Strip type	Packing qty	Carton size	Gross weight/carton
IP20	200 reels	31*36*37cm	16.9KG

Yiyun Corporation Pty Ltd | All information in this catalogue is subject to change at business discretion.
Please contact the office for confirmation of pricing and stock availability at time of order