



SHOP SMART. SHOP VALUE
SHOP *differently*



E&E ALL-IN-ONE EASY CONNECT EXIT

PRODUCT RANGE

CODE	DESCRIPTION
CS-EXLEDL	E&E All-in-One Easy Connect Exit
CS-EXLEDLBK	E&E All-in-One Easy Connect Exit - Black Finish



White finish

ORDERING INFORMATION

Carton Qty	5 pieces
Weight	1.5kg (unit) - 7.5kg (box)
Dimension (L x W x H)	355mm x 80mm x 215mm



Black finish

TECHNICAL SPECIFICATIONS

Operating Mode	Maintained
Voltage (V); Frequency (Hz)	220-260V; 50Hz
Operating Temperature	1° - 45° C
IP Rating	IP20
Wiring	Large Terminal Block
Mounting Type	Wall or Ceiling Surface Mount
Testing System	Manual Test Switch
Construction	Polycarbonate Body and Diffuser
Classification	C0 E2 C90 E2
Standards	AS/NZ 2293 AS/NZS 60598.1 EMC

BATTERY AND LEDS

Battery	High-Temp LiFePO4 Lithium Battery
Power Consumption	3W
Charging Method	3 Stage Intelligence
Charging Time	16 Hours
Lens	LED Lamp Rated at 50,000 Hours
Viewing Distance	24 Metres

REPLACEMENT PART

PART NUMBER	DESCRIPTION
BLEDL	LiFePO4 Lithium Battery, 3.2V 1600mAh



MOORABBIN
131-133 Keys Road
Moorabbin VIC 3189

ALTONA
1 Drake Boulevard
Altona VIC 3018

EPPIING
103 Gateway Blvd
Epping VIC 3076

ALBION
35 Sandgate Road
Albion QLD 4010

AUCKLAND
10 Fairfax Avenue, Penrose
Auckland 1061, New Zealand

sales@jh.market
www.jh.market
sales@jhmarket.co.nz
jhmarket.co.nz

AU National: 1300 000 808
Queensland: 1300 000 707
NZ National: 0800 748 848

Yiyun Corporation Pty Ltd | All information in this catalogue is subject to change at business discretion.
Please contact the office for confirmation of pricing and stock availability at time of order