



SHOP SMART. SHOP VALUE
SHOP *differently*



E&E 6W LED WALL OR CEILING JUMBO 40M MAINTAINED EXIT

PRODUCT RANGE

PRODUCT CODE	CS-EX.JUMBO40ML
Description	E&E 6W LED Wall or Ceiling Jumbo 40M Maintained Exit

ORDERING INFORMATION

Carton Qty	3 pieces
Weight	5.5kg (unit) - 16.5kg (box)
Dimension (L x W x H)	630mm x 100mm x 330mm



TECHNICAL SPECIFICATIONS

Operating Mode	Maintained
Voltage (V); Frequency (Hz)	220-260V; 50Hz
Operating Temperature	1° - 45° C
IP Rating	IP20
Wiring	Large Terminal Block
Mounting Type	Wall or Ceiling Mount
Testing System	Manual Test Switch
Construction	Powder-Coated Metal Frame with Polycarbonate Diffuser
Classification	C0 D5 C90 N/A
Standards	AS/NZ 2293 AS/NZS 60598.1 EMC

BATTERY AND LEDS

Battery	High-Temp LiFePO4 Lithium Battery
Power Consumption	6W
Charging Method	3 Stage Intelligence
Charging Time	16 Hours
Lens	LED Lamp 50,000 Hours
Viewing Distance	40 Metres

REPLACEMENT PART

PART NUMBER	DESCRIPTION
BJUMBOL	LiFePO4 Lithium Battery, 6.4V 3000mAh

SPACING TABLE AND MOUNTING HEIGHT

CLASSIFICATION	2.1m	2.4m	2.7m	3m	3.3m	3.6m	4m	4.5m	5m
E5	6.6	7.0	7.4	7.7	7.9	8.1	8.2	8.2	8.0



MOORABBIN
131-133 Keys Road
Moorabbin VIC 3189

ALTONA
1 Drake Boulevard
Altona VIC 3018

EPPIING
103 Gateway Blvd
Epping VIC 3076

ALBION
35 Sandgate Road
Albion QLD 4010

AUCKLAND
10 Fairfax Avenue, Penrose
Auckland 1061, New Zealand

sales@jh.market
www.jh.market
sales@jhmarket.co.nz
jhmarket.co.nz

AU National: 1300 000 808
Queensland: 1300 000 707
NZ National: 0800 748 848

Yiyun Corporation Pty Ltd | All information in this catalogue is subject to change at business discretion.
Please contact the office for confirmation of pricing and stock availability at time of order